

PD2500U05

Preliminary Datasheet




Power Divider/Combiner

3-Way 0° 50Ω 1.7-3.6GHz



Features

- Small Size (2×2mm DFN package)
 - GaAs
 - No need external 100 Ω resistor
 - Very Low Loss
 - Tight Amplitude Balance
 - High Isolation
 - Low VSWR
 - Good Repeatability
 - High ESD level*
- Operating Temperature -40°C~105°C
- Power handling
- 2.5 Watts as a divider
 - 0.8 Watts as a combiner



TOP VIEW

Applications

- WIMAX
- ISM
- Instrumentation
- Radar
- Satellite communications
- 5G

Notes:

1. This part has passed through 100% RF test.

* ESD rating

Human body model (HBM): Class 2 (2000 to <4000V) in accordance with ANSI/ESD 5.1-2007

Machine model: Class M3 (200 to <4000V) in accordance with ANSI/ESD 5.2-2009

Yantel Corporation

Add: No.308-322, 3F, Building 1, Juchuang Jingu Innovation Park, Wenyuan Road 35, Xili Street, Nanshan, Shenzhen, China

Tel: 86-755-8355-1886 Fax: 86-755-8355-2533

PD2500U05

Preliminary Datasheet

Power Divider/Combiner




3-Way 0° 50Ω 1.7-3.6GHz



Electrical Specifications at 25° C

Parameter	Symbol	Min	Typ	Max	Unit
Frequency Range	F	1.7		3.6	GHz
Insertion Loss (Above 5dB)	I_L		0.77	1.3	dB
Isolation	Isol	11.5	22		dB
Phase balance	ϕ_{bal}		5.2	11.5	deg
Amplitude balance	A_{bal}		± 0.20	± 0.55	dB
Input VSWR			1.30	1.65	
Output VSWR			1.30	1.45	

Typical Performance (-55°C, 25°C, 105°C: 1.7-3.6GHz)



Yantel Corporation

Add: No.308-322, 3F, Building 1, Juchuang Jingu Innovation Park, Wenyuan Road 35, Xili Street, Nanshan, Shenzhen, China







Tel: 86-755-8355-1886 Fax: 86-755-8355-2533

PD2500U05

Preliminary Datasheet

Power Divider/Combiner

3-Way 0° 50Ω 1.7-3.6GHz



Yantel Corporation

Add: No.308-322, 3F, Building 1, Juchuang Jingu Innovation Park, Wenyuan Road 35, Xili Street, Nanshan, Shenzhen, China

Tel: 86-755-8355-1886 Fax: 86-755-8355-2533

Rev A1.0

For detailed performance specs & shopping online see Yantel web site : www.yantel-corp.com

PD2500U05


Preliminary Datasheet

Power Divider/Combiner


3-Way 0° 50Ω 1.7-3.6GHz



Outline Drawing




Land Pattern



Recommended Land Pattern Top View

Notes: All dimensions show in millimeters

Pin Out



Notes:

1. Require to add Capacitors of DC Blocker between Pins(with black color) and external circuit to prevent DC signal entry to guarantee parts normal work.
2. This part has passed through 100% RF test.

Pin #	Connection
1	OUT1
2	IN/SUM
3	GND
4	GND
5	OUT3
6	OUT2

Yantel Corporation

Add: No.308-322, 3F, Building 1, Juchuang Jingu Innovation Park, Wenyuan Road 35, Xili Street, Nanshan, Shenzhen, China

Tel: 86-755-8355-1886 Fax: 86-755-8355-2533